

1. General description

Assists with assembly of rough threaded parts and sliding steel surfaces.

2. Features

- Prevents seizing.
- Takes up high loads.
- Supports extreme slow movements.
- Smoothens rugged surfaces.
- High temperature resistance.

3. Applications

- Rugged thread.
- Guide rails.
- Assembly of rugged parts.
- Sliding surfaces.

4. Directions

- Shake well before use.
- Use only with adequate ventilation.
- Do not use on energized equipment.
- Apply to a clean, dry surface.
- Apply the quantity as described by the machine manufacturer.
- Do not mix with other products.
- To remove residues or excess product, use one of the CRC cleaners.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**


5. Typical product data (without propellant)

Appearance	Paste.
Color	Grey.
Odor	Characteristic odor.



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com





Density	0.731 g/cm ³ (@ 20°C).
4-ball weld load active product	800 kg
4-ball wear active product	0.4 mm
Operating temperature active product	-10 -->600 °C
Copper Corrosion (DIN 51 759)	1a
Steel corrosion (ASTM D 130-83)	0-1

6. Packaging

Aerosol	12x500 ML	Ref. : 32147
---------	-----------	--------------

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_GREEN-ALU_PASTE-20140228

Date



Manufactured by :
CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele Belgium
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34
www.crcind.com

