

Anti Spatter

1. General description

Traditional solvent and biodegradable oil based spatter release. Non-flammable for increased safety. Saves cleaning time by preventing spatter adhesion on welding equipment, work pieces and jigs. Does not contain silicones (use CRC Bio Weld for problem free galvanizing).

2. Features

- Economical in use, due to the thin film performance.
- Extended nozzle stand time and increased stability of the welding arc, ensuring free gas flow.
- Does not contain silicones.
- Based on non flammable solvents.
- Non corrosive.
- Protects metals and alloys.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO2 propellant, giving an active product content of 95%.

3. Applications

- Welding equipment.
- Manual, semi-automatic welding equipment as well as welding robots.

4. Directions

- Apply a thin even film.
- Spatters can be removed with a wire brush.
- If post treatment involves Hot Dip Galvanising, follow the cleaning instructions from the galvanizing company or the galvanizing federations (info via International Zinc Association: www.iza.com)
- Protect aerosol against heat sources, welding spatters, etc...
- Use only with adequate ventilation.
- To remove residues or excess product, use one of the CRC cleaners.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

5. Typical product data (without propellant)

Appearance	Aerosol Liquid.	Bulk Liquid.
Color	Colorless.	Colourless to yellow.
Odor	Characteristic odor.	Characteristic odor.
Density	1.123 g/cm ³ (@ 20°C).	1.292 g/cm ³ (@ 20°C).
Flash Point	None	None
Density active product	0.92 g/cm ³ (@ 20°C).	0.92



Technical Data Sheet

Anti Spatter

Flash point active product	290 °C (Closed Cup)	290 °C
Typical coat weight	2 - 5 µm	2 - 5 µm

Remarks

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

Version CRC_GREEN-ANTI_SPATTER-20190405
Date 05/04/2019